



7872

### Digiality CX-CI 422 TS Combo PVR

#### PRODUCT VISUAL



#### PRODUCT DESCRIPTION

Digital Satellite & Terrestrial Receiver with PVR option

#### FEATURES

- Combo receiver (two tuners, satellite and terrestrial)
- Embedded Conac CAS5
- One card reader
- 2 Scart connections
- 3000 Channels
- On screen graphic display available in: English, Danish, Swedish, Norwegian and Finnish
- 1 Common Interface slot for CA-modules
- 4 days Electronic Programme Guide
- Video timer; 8 takes over 28 days
- PVR Option (40, 60 or 80 GB) - 2,5" Plug & Play solution
- 4 favourite programme lists, extremely easy to use
- Satellite and terrestrial programmes in one programme list
- More than 4000 pages of fast teletext
- Modulator (Ch. 21 - 69)
- SPDIF / Dolby Digital™
- Programmable shortcut keys on the remote control
- Software update by air (OTA)
- Receiver hardware and software developed in Denmark

#### TECHNICAL SPECIFICATIONS

##### Conditional Access Interface

Embedded crypt.: Conax  
PCMCIA: 1 x CI slot(s)

##### Tuner & Channel

Input connector: Terrestrial: 75 Ohm, IEC 169,2;  
Satellite: F- Type  
Input frequency range: Terrestrial: 174 to 862 MHz;  
Satellite: 950 - 2200 MHz  
Input impedance: 75 Ohm  
Wave form: QFDM  
Signal level: -65 to -25 dBm  
Mode: 2K, 8K

Codes Rates: Automatic  
Guard intervals: Automatic

##### LNB supply

Vertical: + 13 V  
Horizontal: + 18 V  
Current: Max. 500 mA  
22 KHz Tone: 22 +/- 4 KHz  
DiSEqC control: Version: 1.1 and Stab USALS motor control  
Demodulation: QPSK  
Symbol rate: 2.5 - 40 Ms/s  
FEC Decoder: Automatic

##### MPEG Transport Stream A/V Decoding

Transport stream: MPEG-2 ISO/IEC 13818  
Profile level: MPEG-2 MP@ML  
Aspect ratio: 4:3 / 16:9 / Letterbox  
Audio decoding: MPEG Layer I & II  
Video resolution: 720 x 576  
Audio mode: Mono, Stereo, Dolby Digital™

##### A/V Data In/Out

Video output: TV Scart (CVBS, RGB)  
VCR Scart (CVBS)  
Video input: (CVBS, RGB)  
Audio output: Audio L/R RCA/Cinch volume and mute control;  
S/PDIF  
RS232: 9 pin D-sub

##### RF Modulator

RF connector: 75 Ohm, IEC 169-2  
TV standard: PAL B/G, D/K, I  
RF Output channel: CH 21 - 69  
Preset channel: CH 38

##### Processor and Memory

Processor: Integrated 32-bit host CPU @ 160 MHz  
System SDRAM: 16 Mbyte  
Flash memory: 2 Mbyte

##### OPTION: Digital Video Recorder (PVR)

Hard disc: 40, 60 or 80 GB