

Tekniske specifikationer vnr.: 04249

Satlook Mrk. IV FTA

frequency: 950-2150MHz.

Min level in: About 30 dBuV (noise).

Max level in: About 100 dBuV.

TV/Audio standard: PAL.

Input impedance: 75 Ohm, BNC-con.

Picture-screen: 4" Color TFT monitor

KU- C-band: Yes, selectable.

Audio bandwidth : Adjustable between 5.5 MHz and 8.5 MHz

Measuring method: 1. Full spectrum, normal or expanded mode.

2. 4" monitor with full picture. Optional with pos/neg video.

3. Level check on single channel with LED-bar display.

4. Level check with audio from loudspeaker.

5. FTA Digital signal readout.

Max level: Spectral with max peaks.

Two digits LED display with max value.

LED bar with max indication.

Highest tone from loudspeaker.

FTA Digital max signal.

Supply voltage LNB: 13-18V, switchable

Tone switch: 22 KHz. On / Off.

DiSEqC: Standard DiSEqC, level 1.0.

Output: Video and Audio output for connection to TV / monitor.

Operational: About 1 hour on a fully charged battery.

Weight: Aprox. 5.5 kg incl.battery.

Power supply: Internal rechargeable battery 12V 3.0

Amp. External power supply, In: 100-

230V. Output 13.5V 1.5 amp DC. Caradaptor.

Accessories: Nylon carrying-case.

Adaptor BNC / F-connector.

Remote control for FTA set-top box.

User Manual.